

# Underground Diesel Loader



Highly Intelligent



Safe and Reliable



High Stability



Profitability Enhancement

# Underground Diesel Loader

Item		SL07	SL10	SL14
Standard bucket (m <sup>3</sup> )		3.5	4	6
Dimension (mm)	Length	9,170	9,790	10,690
	width	2,280	2,580	2,870
	height	2,240	2,375	2,590
Rated Load (kg)		7,000	10,000	14,000
Ground Clearance (mm)		313	380	390
Wheelbase (mm)		3,160	3,500	3,600
Turning Radius (Inner) (mm)		2,285	3,310	3,325
Turning Radius (Outer) (mm)		5,950	6,550	6,825
Unloading Height (mm)		1,715	2,180	2,375
Unloading Distance (mm)		1,610	1,480	1,440
Maximum Speed (km/h)		23	30	28
Gradeability (%)		25	25	25
Diesel Engine Power (kW)		160	235	285
Diesel Engine Torque (Nm)		1,060	1,580	1,965
Emission Standard		Euro stage III	Euro stage III	Euro stage III



## Hubei Shentuo Intelligence Equipment Co., Ltd.

Tel: +86 177 5920 3094 / +86 722 3826690

WhatsApp: +86 177 5920 3094

E-mail: [info@emsuntour.com](mailto:info@emsuntour.com)

Website: [uk.emsuntour.com](http://uk.emsuntour.com)

Address: Building 3, No. 789, Jiaotong Avenue, Zengdu District, Suizhou City, Hubei Province, China